

Safety Data Sheet

STARFIRE Premium Plus Syn blend **15W-40 CK-4**

Revision Date: 02-13-2019

1. Identification

Product identifier used on the label: STARFIRE Premium Plus Synthetic Blend **15W-40 CK-4**
Product Code: 644

Other means of identification:

Synonyms: No data available

Recommended use of the chemical and restrictions on use:

Recommended use: Motor Oil

Restrictions on use: Uses other than those described above

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party: PennStar
6 Horwith Dr.
Northampton, PA 18067

Phone number: +01 (484) 275-7990

Emergency phone number: CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Classification: Not classified as hazardous under OSHA

Hazards not otherwise classified: No data available

% unknown toxicity (Oral): 12.622746 % of the mixture consists of ingredient(s) of unknown toxicity.

% unknown toxicity (Dermal): 12.614794 % of the mixture consists of ingredient(s) of unknown toxicity.

% unknown toxicity (Inhalation Gas): 98.681913 % of the mixture consists of ingredient(s) of unknown toxicity.

% unknown toxicity (Inhalation Dust): 98.701715 % of the mixture consists of ingredient(s) of unknown toxicity.

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS #	%
Petroleum distillates, solvent dewaxed heavy paraffinic	No data available	64742-65-0	0.5 - 1.5

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Safety Data Sheet

STARFIRE Premium Plus Syn blend 15W-40 CK-4

Revision Date: 02-13-2019

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.
Eye Contact:	Use eye wash to remove a chemical from the eye. Flush the affected eye for at least fifteen minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical attention if irritation persists.
Skin Contact:	Wash with soap and water. Get medical attention if irritation develops or persists.
Ingestion:	No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.

Most important symptoms/effects, acute and delayed:

Indication of immediate medical attention and special treatment needed, if necessary:

No additional first aid information available.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.

Unsuitable extinguishing media: No data available

Specific hazards arising from the chemical:

No data available

Hazardous combustion products:

Carbon monoxide, Sulfur containing gases, Nitrogen containing gases, Aldehydes, oxides of phosphorus, Hydrogen sulfide, Smoke

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.

Safety Data Sheet

STARFIRE Premium Plus Syn blend 15W-40 CK-4

Revision Date: 02-13-2019

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: No health effects expected from the clean up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this SDS.

Methods and materials for containment and cleaning up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center.

7. Handling and storage

Precautions for safe handling: Mildly irritating material. Avoid unnecessary exposure. Follow all protective equipment recommendations provided in Section 8.

Conditions for safe storage, including any incompatibilities:

Safe storage conditions: Store in a cool dry place. Isolate from incompatible materials.

Materials to Avoid/Chemical Incompatibility: Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m ³	5 mg/m ³	10 mg/m ³	No data available
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	5 mg/m ³	5 mg/m ³	10 mg/m ³	No data available
Petroleum distillates, solvent dewaxed heavy paraffinic	5 mg/m ³	5 mg/m ³	10 mg/m ³	No data available

Appropriate engineering controls: Use local exhaust ventilation or other engineering controls to minimize

